ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



## MATERIAL SAFETY DATA SHEET

### **ACETONE 99% Extra Pure**

(For Synthesis)
MSDS CAS: 67-64-1

## **Section 1: Chemical Product and Company Identification**

**Section 1: Chemical Product** 

**Product Name: Acetone** 

CAS#: 67-64-1

Synonym: 2-propanone; Dimethyl Ketone; Dimethylformaldehyde; Pyroacetic Acid.

Chemical Name: Acetone. Chemical Formula: C<sub>3</sub>H<sub>6</sub>O

**Brand: OXFORD** 

### **Details Of The Supplier Of The Safety Data Sheet:**

**Company identification: OXFORD LAB FINE CHEM LLP** 

Unit. No. 12, 1st Floor, Neminath Industrial Estate No. 6,

Navghar, Vasai (East). Palghar - 401 210.

Mumbai, Maharashtra, INDIA.

Tel: 91-250-2390989

Tel/Fax: 91-250-2390032

## **Section 2: Composition and Information on Ingredients**

#### **Composition:**

Name	CAS#	% by Weight
Acetone	67-64-1	100

<u>Toxicological Data on Ingredients</u>: Acetone: ORAL (LD50): Acute: 5800 mg/kg [Rat]. 3000 mg/kg [Mouse]. 5340 mg/kg [Rabbit]. VAPOR (LC50): Acute: 50100 mg/m 8 hours [Rat]. 44000 mg/m 4 hours [Mouse].

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



# Section 3: Hazards Identification

<u>Potential Acute Health Effects</u>: Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

<u>Potential Chronic Health Effects</u>: CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED]. The substance is toxic to central nervous system (CNS). The substance maybe toxic to kidneys, the reproductive system, liver, skin. Repeated or prolonged exposure to the substance can produce target organs damage.

### **Section 4: First Aid Measures**

**Eye Contact**: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Get medical attention.

<u>Skin Contact</u>: In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

<u>Serious Skin Contact</u>: Wash with a disinfectant soap and cover the contaminated skin with an antibacterial cream. Seek medical attention.

<u>Inhalation:</u> If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.

<u>Serious Inhalation</u>: Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.

<u>Ingestion:</u> Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

**Serious Ingestion**: Not available.

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



### **Section 5: Fire and Explosion Data**

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 465°C (869°F).

Flash Points: CLOSED CUP: -20°C (-4°F). OPEN CUP: -9°C (15.8°F) (Cleveland).

Flammable Limits: LOWER: 2.6% UPPER: 12.8%.

**Products of Combustion:** These products are carbon oxides (CO, CO2).

Fire Hazards in Presence of Various Substances: Highly flammable in presence of open flames and sparks, of heat.

Explosion Hazards in Presence of Various Substances: Risks of explosion of the product in presence of mechanical impact: Not available. Slightly explosive in presence of open flames and sparks, of oxidizing materials, of acids.

Fire Fighting Media and Instructions: Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog.

Special Remarks on Fire Hazards: Vapor may travel considerable distance to source of ignition and flash back.

Special Remarks on Explosion Hazards: Forms explosive mixtures with hydrogen peroxide, acetic acid, nitric acid, nitric acid + sulfuric acid, chromic anydride, chromyl chloride, nitrosyl chloride, hexachloromelamine, nitrosyl perchlorate, nitryl perchlorate, permonosulfuric acid, thiodiglycol + hydrogen peroxide, potassium ter-butoxide, sulfur dichloride, 1-methyl-1,3-butadiene, bromoform, carbon, air, chloroform, thitriazylperchlorate.

# Section 6: Accidental Release Measures

#### Small Spill:

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

#### **Large Spill:**

Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

## **Section 7: Handling and Storage**

### **Precautions:**

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



## **Section 7: Handling and Storage (Continued)**

Keep locked up.. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, reducing agents, acids, alkalis.

<u>Storage:</u> Store in a segregated and approved area (flammables area). Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Keep away from direct sunlight and heat and avoid all possible sources of ignition (spark or flame).

## Section 8: Exposure Controls/Personal Protection

#### **Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

#### **Personal Protection:**

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

#### Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits: TWA: 500 STEL: 750 (ppm) from ACGIH (TLV) [United States] TWA: 750 STEL: 1000 (ppm) from OSHA (PEL) [United States] TWA: 500 STEL: 1000 [Austalia] TWA: 1185 STEL: 2375 (mg/m3) [Australia] TWA: 750 STEL: 1500 (ppm) [United Kingdom (UK)] TWA: 1810 STEL: 3620 (mg/m3) [United Kingdom (UK)] TWA: 1800 STEL: 2400 from OSHA (PEL) [United States] Consult local authorities for acceptable exposure limits.

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



## **Section 9: Physical and Chemical Properties**

Physical state and appearance : Liquid.

Odor : Fruity. Mint-like. Fragrant. Ethereal.

Taste : Pungent, Sweetish.

Molecular Weight : 58.08 g/mole.

Color : Colorless. Clear.

pH (1% soln/water) : Not available.

Boiling Point  $: 56.2^{\circ}\text{C} (133.2^{\circ}\text{F}).$ 

**Melting Point** : -95.35 (-139.6°F)

Critical Temperature : 235°C (455°F).

Specific Gravity : 0.79 (Water = 1) Vapor Pressure : 24 kPa (@ 20°C)

Vapor Pressure : 24 kPa (@ 20°C) Vapor Density : 2 (Air = 1)

Volatility : Not available.

Odor Threshold : 62 ppm.

Water/Oil Dist. Coeff. : The product is more soluble in water; log(oil/water) = -0.2

**Ionicity (in Water)** : Not available.

**Dispersion Properties** : See solubility in water.

**Solubility** : Easily soluble in cold water, hot water.

# **Section 10: Stability and Reactivity Data**

**Stability** : The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Excess heat, ignition sources, exposure to moisture, air, or water, incompatible

materials.

Incompatibility with various substances: Reactive with oxidizing agents, reducing agents, acids, alkalis.

Corrosivity : Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available. Special Remarks on Corrosivity: Not available.

**Polymerization** : Will not occur.

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



## **Section 11: Toxicological Information**

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Inhalation.

Toxicity to Animals: WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 3000 mg/kg [Mouse]. Acute toxicity of the vapor (LC50): 44000 mg/m3 4 hours [Mouse].

Chronic Effects on Humans: CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED]. Causes damage to the following organs: central nervous system (CNS). May cause damage to the following organs: kidneys, the reproductive system, liver, skin.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: May affect genetic material (mutagenicity) based on studies with yeast (S. cerevisiae), bacteria, and hamster fibroblast cells. May cause reproductive effects (fertility) based upon animal studies. May contain trace amounts of benzene and formaldehyde which may cancer and birth defects. Human: passes the placental barrier.

#### **Special Remarks on other Toxic Effects on Humans:**

Acute Potential Health Effects: Skin: May cause skin irritation. May be harmful if absorbed through the skin. Eyes: Causes eye irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. Inhalation: Inhalation at high concentrations affects the sense organs, brain and causes respiratory tract irritation. It also may affect the Central Nervous System (behavior) characterized by dizzness, drowsiness, confusion, headache, muscle weakeness, and possibly motor incoordination, speech abnormalities, narcotic effects and coma. Inhalation may also affect the gastrointestinal tract (nausea, vomiting). Ingestion: May cause irritation of the digestive (gastrointestinal) tract (nausea, vomiting). It may also affect the Central Nevous System (behavior), characterized by depression, fatigue, excitement, stupor, coma, headache, altered sleep time, ataxia, tremors as well at the blood, liver, and urinary system (kidney, bladder, ureter) and endocrine system. May also have musculoskeletal effects. Chronic Potential Health

## **Section 12: Ecological Information**

Effects: Skin: May cause dermatitis. Eyes: Eye irritation.

Ecotoxicity: Ecotoxicity in water (LC50): 5540 mg/l 96 hours [Trout]. 8300 mg/l 96 hours [Bluegill]. 7500

mg/l 96 hours [Fatthead Minnow]. 0.1 ppm any hours [Water flea].

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



## Section 12: Ecological Information (Continued)

**BOD5** and **COD**: Not available.

#### **Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise..

<u>Toxicity of the Products of Biodegradation</u>: The product itself and its products of degradation are not toxic

**Special Remarks on the Products of Biodegradation:** Not available.

## **Section 13: Disposal Considerations**

Waste Disposal: Waste must be disposed of in accordance with federal, state and local environmental control regulations.

## **Section 14: Transport Information**

#### **Land transport (ADR-RID)**

**Proper shipping name: ACETONE** 

UN N° : 1090 H.I. nr : 33 ADR - Class : 3

#### Sea transport (IMDG) [English only]

Proper shipping name : ACETONE

UN  $N^{\circ}$  : 1090

**IMO-IMDG - Class or division: 3: Flammable liquid.** 

**IMO-IMDG - Packing group**: II

#### Air transport (ICAO-IATA) [English only

Proper shipping name : ACETONE

UN  $N^{\circ}$  : 1090

IATA - Class or division : 3: Flammable liquid.

IATA - Packing group : II

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



## **Section 15: Other Regulatory Information**

Federal and State Regulations: California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (male) which would require a warning under the statute: Benzene California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Benzene California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Benzene, Formaldehyde Connecticut hazardous material survey.: Acetone Illinois toxic substances disclosure to employee act: Acetone Illinois chemical safety act: Acetone New York release reporting list: Acetone Rhode Island RTK hazardous substances: Acetone Pennsylvania RTK: Acetone Florida: Acetone Minnesota: Acetone Massachusetts RTK: Acetone Massachusetts spill list: Acetone New Jersey: Acetone New Jersey spill list: Acetone Louisiana spill reporting: Acetone California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

#### **Other Classifications:**

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC).

#### **DSCL (EEC):**

R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from sources of ignition - No smoking. S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

HMIS (U.S.A.): Health Hazard: 2 Fire Hazard: 3 Reactivity: 0

Personal Protection: h

**National Fire Protection Association (U.S.A.):** 

Health: 1

Flammability: 3 Reactivity: 0 Specific hazard:

**Protective Equipment:** 

Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor, Neminath Industrial Estate No.6, Navghar, Vasai (East), Palghar - 410210. Maharashtra, INDIA. Tel: +91 250 2390032 / 2390989 / 2390990 Email: sales@oxfordlabchem.com / info@oxfordlabchem.com Web: www.oxfordlabchem.com



# **Section 16 - Additional Information**

**References**: Not available.

Other Special Considerations: Not available.

### Disclaimer:

The information contained herein in good faith but makes no representations as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Oxford Lab Fine Chem LLP makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, Oxford Lab Fine Chem LLP will not be responsible for damages resulting from use of or reliance upon this information.